

T 3

Tuner

The 3 Series

Parasound's Halo T 3 Tuner is the ultimate combination of cutting edge technology, superb craftsmanship, and stunning industrial design. Complete with RDS, balanced XLR outputs, RS-232 control, and a remote with direct frequency access, the T 3 is easy to operate and install in any system. It's remarkable design delivers pristine sound quality from stations you may have never been able to receive before, and it looks as amazing as it sounds. The T 3 tuner solidifies our reputation for delivering high quality tuners for critical listening and custom installation.



Features

- 60 station presets with Auto-Memory feature
- Seek, manual, and preset tuning with RDS
- Direct frequency access via remote and RS-232
- Two-way RS-232 Serial Port connection
- Balanced outputs with XLR connectors
- Enormous encapsulated toroid power transformer
- Dual layer glass epoxy circuit boards
- Multi-region European operation
- External IR input and loop output jacks
- Two 12v triggers; 1 input and 1 loop output
- Gold-plated RCA output jacks
- Fully remote controlled
- Remote control also operates P 3 Preamplifier
- Robust 2u Chassis, rack mounting adapter available
- Parasound's 10 years parts, 5 years labor warranty

Specifications

- FM sensitivity: Mono - IHF 11 dBf
- Stereo- IHF 37.2 dBf for 50 dB of quieting
- AM sensitivity: IHF 10 μ V/m
- Signal to noise ratio: FM > 74 dB stereo, AM > 45 dB
- FM stereo separation: 50 dB @ 1 kHz; 40 dB @ 10 kHz
- Selectivity: FM 80 dB; AM 30 dB
- FM frequency response: 30 Hz - 15 kHz +/- 1 dB
- AM frequency response: 20 Hz - 5.5 kHz +/- 2 dB
- Total harmonic distortion: FM Mono < 0.08%;
- FM Stereo < 0.2%; AM < 1%
- Capture ratio: < 1.5 dB
- AM Suppression: 60 dB
- Voltage: Switchable for 110V - 120V or 220V - 240V operation
- Dimensions: 17-1/4" w x 4-1/8" h x 13-3/4" d, 3-5/8" h without feet
- Net weight: 15 lbs.

