

## Contractor Series In-Ceiling Speakers

# CST-65R/CSS-60R



### Features

#### CST-65R

6-1/2" Polycarbon woofer with 1-1/2" voice coil,

3/4lb. magnet and Polyurethane surround

Pivoting 1" titanium dome tweeter that utilizes

ferrofluid for damping/cooling

Three element 12 dB/octave 2.6 kHz crossover

#### CSS-60R

6-1/2" reinforced paper, full range woofer with

1" voice coil, 1/2lb. magnet and Polyfoam surround

Passive high frequency radiator

#### Both

Woven dust screen to protect woofer from in-wall debris

Acoustically transparent, fine mesh grill with paint shield

Four point, spring-loaded "dog-leg" mounting system

Parasound's 10 years parts and labor warranty

**Parasound's Contractor Series** of in-ceiling speakers effectively combines excellent quality with value engineering. The CST-65R and CSS-60R provide plenty of bass with a 6-1/2" woofer, allow installation in minutes with our convenient "dog-leg" mounting system, and boast a ten year warranty. The CST-65R even offers a pivoting pure titanium tweeter to assure the musical sweet spot is exactly where you want it to be. With the Contractor Series from Parasound, you can fill your home and office with amazing sound without emptying your pocketbook.

### Specifications

Frequency response:

58 Hz - 20 kHz +/- 3 dB (CST-65R)

60 Hz - 18 kHz +/- 3 dB (CSS-60R)

Nominal/ Minimum impedance: 8Ω/ 6Ω

Sensitivity:

88 dB 1 watt/1 meter (CST-65R)

87 dB 1 watt/1 meter (CSS-60R)

Power range:

10 - 60 watts (CST-65R)

10 - 40 watts (CSS-60R)

Woofer size: 6-1/2"

Woofer cone material:

Polycarbon (CST-65R)

Reinforced paper (CSS-60R)

Surround material:

Polyurethane (CST-65R)

Polyfoam (CSS-60R)

Tweeter size/material: 1" titanium dome (CST-65R)

Cut-out hole dimensions: 7-3/4"

Outer edge of frame: 9"

Optional NCK-3M New Construction Kit



## PARASOUND

Parasound Products, Inc. 950 Battery Street, San Francisco, CA 94111

415-397-7100 / FAX 415-397-0144 [www.parasound.com](http://www.parasound.com)