
Z Series Specialty Components

Zamp v.2







What is Parasound's Z-Series? It's the highest-fidelity set of matched miniatures available today. Only 2" tall and 9-1/2" wide, Z's can stand alone on the smallest surface, or rack mount side by side. Wherever you want a minimum-size system with maximum-quality sound — on desktop, counter, inwall or multi-zone — the Z-Series is your compact sonic solution.

Features

30 watts per channel into 8Ω

45 watts per channel into 4Ω

90 watts bridged into 8Ω mono

Gain controls and bridge switch on rear panel

Automatic on/off by DC trigger or audio signal

Ground lift switch

Looping line output connectors

Headphone jack

LED indicators for AC present and operating mode

Gold-plated RCA input jacks and 5-way speaker terminals

High-current Torrodial power supply

9-1/2" wide front panel; I rack space high

Fastening hardware available for rack mounting

Parasound's 10 years parts, 5 years labor warranty

Specifications

Continuous power output:

30 watts RMS x 2, 20 Hz - 20 kHz, 8Ω , both channels driven

45 watts RMS x 2, 20 Hz - 20 kHz, 4Ω , both channels driven

75 watts RMS x 1,20 Hz - 20 kHz,8 Ω , minimum impedance

Current capacity: 10 amperes peak per channel

Frequency response: 5 Hz - 100 kHz, +0/-3 dB

Total harmonic distortion: < 0.06 % full power;

< 0.03 % typical levels

IM distortion: < 0.03 %

Dynamic headroom: > 1.5 dB

Inter-channel crosstalk: > 80 dB at 1 kHz; > 60 dB at 20 kHz

Input impedance: 33 $k\Omega$

S/N ratio: > 100 dB, input shorted, IHFA weighted

Dimensions: 9-1/2" w x 2" h x 7" d, 1-3/4" h without feet

Shipping weight: 9 lbs.

