

Mini Z Components

Ztuner

The Ztuner receives even the remotest stations clean and clear without taking up much space. Whether you are using one Ztuner or up to four, a single remote is all you need. For a mini system or the most elaborate home system, the Ztuner is the perfect choice.



Features

- Automatic, manual, and preset tuning
- Two-way RS-232 serial port connection
- Direct frequency access via remote and RS-232
- Thirty station presets, switchable to eight for quicker scrolling
- Forced Mono operation for mono zones
- Remote handset assignable up to four different zones
- Automatic on/off by 9 - 12 V trigger, with looping output
- Fully remote controlled with discrete on/off commands
- Rear panel infrared remote input and looping output
- Gold-plated RCA output jacks
- Multi-region European operation
- Voltage switchable between 115v and 230v
- Unique half-rack width chassis; 1 rack space high
- Fastening hardware available for rack mounting
- Parasound's 10 years parts, 5 years labor warranty

Specifications

- Tuning range: FM 87.5 MHz to 108 MHz; AM 520 kHz to 1610 kHz
- FM sensitivity: Mono - IHF 10.8 dBf
 - Stereo - IHF 36.9 dBf for 50 dB of quieting
- AM sensitivity: IHF 10 μ V/m
- S/N ratio: 74 dB stereo; 65 dB IHF weighted
- FM stereo separation: 50 dB @ 1 kHz; 40 dB @ 10 kHz
- Selectivity: FM, 80 dB; AM, 30 dB
- FM frequency response: 30 Hz - 15 kHz +/- 1 dB
- AM frequency response: 20 Hz - 4.5 kHz +/- 2 dB
- Total harmonic distortion: FM Mono <0.08%; FM Stereo < 0.18%
 - AM < 0.5%
- Capture ratio: 1.5 dB
- AM suppression: 60 dB
- Dimensions: 9-1/2" w x 1-3/4" h x 10" d, 2" h with feet
- Net weight: 4 lbs.



PARASOUND

Parasound Products, Inc. 950 Battery Street, San Francisco, CA 94111
415-397-7100 / FAX 415-397-0144 www.parasound.com